



Industrial strength



Powder Coat options*



Low/high cycle Spring/springless options*



Smooth operation



High-wind resistant

INTERLOCKING 75MM AND 100MM SLATS, CONSTRUCTED WITH GALVANISED G300 BLUESCOPE STEEL WITH 275 ZINC COATING AND ROLL FORMED IN-HOUSE.

Made in Australia by ECO Garage Doors industrial division, ECO Industrial roller shutter doors add style, functionality and strength to any building. Manufactured from galvanised G300 Bluescope steel with Z275 zinc coating, ECO Industrial roller shutters are designed and engineered to stand strong against wind, hail and savage storms.

INDUSTRIAL SPRINGS

Australian / NZ made Industrial Torsion Springs.

AUSTRALIAN STEEL

Roll formed by ECO Industrial Division, and available in 75mm and 100mm profiles.



VENTILATION

Available in perforated or pre-punched profiles adding up to 30% open air.

BOTTOM RAIL

Australian made industrial aluminium bottom rail and heavy duty rubber seal.



DRUM

Australian made Orrcon seamless drum and axle tube with Australian made solid machined steel shafts.



MOUNTING BRACKET

Australian made industrial mounting brackets.

COMMERCIAL & INDUSTRIAL OPENERS

Multiple configuration options to suit an extensive range of applications.

ROLL FORMED TRACKS

Australian made industrial steel guide tracks.

FEATURE AND BENEFITS



Industrial Strength Australian Steel

Made to withstand even the worst weather, ECO makes its industrial roller shutters with interlocking 75mm and 100mm slats, built from galvanised G300 Bluescope steel with Z275 zinc coating for additional strength.



Powder Coat

Choose to have your industrial roller shutters powder coated for a durable factory finish.



Solid Drum

Australian steel seamless drum and tube, solid machined steel shaft.



Operation

An ECO HDS Industrial Electric Opener is available in single or three-phase, depending on your power supply. Remote handsets also available.



Spring Options

Low and high cycle options available to suit individual applications. Your choice depends on whether your industrial roller door is for a high or low traffic area. Choose high cycle for doors that open and close multiple times a day.



Ventilation



ECO industrial roller shutters can be perforated or pre-punched to add ventilation for different applications such as for car parks and canteens.

Perforated slats

Up to 30% open air

Slotted slats

Up to 11% open air



End Clips

ECO industrial roller shutters are made with high quality Australian made plastic end clips, preventing sideways movement while keeping the shutter quiet and reliable.



Bottom Rail

Industrial roller shutters have a unique ECO heavy-duty bottom rail made of 6060t5 extruded aluminium. An additional UV stable weather seal is added to seal against rain, dust and leaves.



Wind Locks

Recommended for doors in high wind areas or for added strength. Wind lock doors come with standard Cast Metal wind lock end clips and wind lock tracks.

AVAILABLE GAUGE AND THICKNESS

75mm	100mm
0.8 x 75mm	0.8 x 100mm
	1.0 x 100mm

eco INDUSTRIAL

MELBOURNE (Head Office)

181-183 Frankston-Dandenong Rd,
Dandenong South Vic 3175

t: (03) 9703 1500

SYDNEY

Unit 6, 72 Lasso Road,
Gregory Hills NSW 2557

t: (02) 8417 8117

sales@ecogaragedoors.com.au | www.ecogaragedoors.com.au

eco
GARAGE
DOORS
welcome home

