



Fire Resistant



Weather Resistant



Corrosion Resistant



Scratch Resistant




Impact Resistant



Salt Resistant




Humidity Resistant



ecogaragedoors Essence Timber Finish is a luxury pre-painted steel product designed to suit Australian high-end Architecture. Combining the world's best coil coating technology with rigorous testing to Australian Standards, it ensures superior performance in the harsh Australian environment.

The Essence Timber Finish uses a hot-dipped aluminium/zinc alloy-coated steel substrate finished with a polyester top coat. The top coat uses infrared reflective pigments and baked on to a polyester primer, delivering an extremely durable painted finish built to resist Australian conditions. Providing excellent colour and gloss retention, the Essence Timber Finish can be easily rollformed to a sectional overhead profile of your choice and is available in 3 colours.

COLOUR OPTIONS



FEATURES AND BENEFITS



CORROSION RESISTANT PRIMER

Athmospheric class C1–C3.



IMPACT RESISTANT

No loss of paint adhesion after a test piece is struck on the reverse side with a specified force of 10J, in line with the test methodology AS/NZS2728:2013.



FIRE RESISTANCE

Meets the requirements of AS/NZS 1530.3 methods for fire tests on building materials.



HUMIDITY RESISTANCE

Humidity resistance - Meets the requirements of AS/NZS2728:2013 Sections 2.8 and 2.9.



SCRATCH RESISTANT

Tested in accordance with AS2331.4.7, with no less than 1.5kg weight applied to the test piece.



SALT SPRAY RESISTANT

Meets the requirements of AS/NZS2728:2013.



QUV RESISTANT (DURABILITY OF COATING)

The Essence timber finish is made using hot dipped aluminium and zinc alloy, delivering excellent durability. Meets the requirements of AS/NZS2728:2013.

Note: tested on a flat panel.



MAINTENANCE FREE#

Unlike real timber that needs to be conditioned and treated to withstand various weather conditions, the Essence timber finish does not require regular maintenance besides standard cleaning.

refer to warranty maintenance



BEND TEST

No loss of adhesion or paint cracking when bent around a diameter equal to five times the thickness of the sheet AS/NZS2728:2013 section 2.6.1 and Appendix F.



FINGER PROTECTION

Finger protection technology will safeguard your family against unforeseen circumstances. Each panel has curved edges to prevent anything, especially fingers, getting caught or trapped in each section as the door opens and closes.

PROFILE OPTIONS

The Essence timber finish is offered in the below Panel lift-safe profiles.



SLIMLINE*



CLASSIC PANEL^



ULTRALINE^



LINCOLN PANEL^

* Essence Timber Finish – Textured finish applies to Slimline profile.

^ Essence Timber Finish – Woodgrain finish applies to Classic, Lincoln and Ultraline profiles.

MELBOURNE (Head Office)

181-183 Frankston-Dandenong Rd,
Dandenong South Vic 3175

t: (03) 9703 1500

SYDNEY t: (02) 8417 8117

PERTH t: (08) 6498 7007

ADELAIDE t: (08) 8185 4998

sales@ecogaragedoors.com.au | www.ecogaragedoors.com.au

eco
GARAGE
DOORS
welcome home

Colour swatches and images shown on Eco Garage Doors website and in this brochure have been reproduced to represent actual product colours as accurately as possible. However, we recommend checking your chosen colour against an actual sample of the product before purchasing as varying light conditions and limitations of the printing process may affect colour tones. Eco Garage Doors is a trademark of Eco Garage Doors. All garage doors are supplied and installed with an Eco Garage Doors trademark badge. ©Copyright Eco Garage Doors. All rights reserved.

