

eco RESIDENTIAL 1000N SDO

Residential Sectional Garage Door Opener



SAFE | RELIABLE | TRUSTED

ECO's 1000N Sectional Garage Door opener is expertly designed to keep you home safe. This super quiet opener is powerful, safe and reliable. Available in either chain or belt drive C-Rail to operate our Panel Lift-Safe and Insulated garage doors. Compliant with Australian and New Zealand standards, you can trust the ECO 1000N Sectional Garage Door opener to operate safely for years.



CONTINUOUS 433MHZ ROLLING CODE

Continuous roller code technology adds interference-free operation to give you peace of mind that no-one can break your code.



SOFT START / STOP

Adjustable open and close speed for reliable, safe and efficient operation (16cm per second). Soft start / soft close function reduces wear and tear on door and associated parts.



AUTO CLOSE

Auto close feature offers the convenience to automatically close in an adjustable time period when fitted with PE safety beam accessory.



AUTOMATIC SAFETY IMPACT SENSOR

Built in obstruction impact sensor will stop door closing on impact and reverse almost immediately to start opening again.



MAINTENANCE ALARM

Alarm notification when maintenance is required on opener.



ACCESSORIES INCLUDED

- › 2 x EC04 remotes

ADD-ON ACCESSORIES*

- › Wireless Wall Button
- › PE Safety Beams
- › Battery Back-up
- › Wireless Keypad
- › Vehicle Sun-Visor Remote
- › Eco Smart available (installation requires PE Beams)



LED LIGHT

Convenient 3 minute LED light automatically illuminates when door is opening or closing.



DRIVE MECHANISM

C-rail with chain or belt available.

Maximum door height: 2400–3500mm Maximum balanced door weight: 100kg.


Compliant to Australian and New Zealand Standard AS/NZS 60335.2.95 with AS/NZS 60335.1



TECHNICAL SPECIFICATIONS

Input voltage	220 – 240V / 110 – 127V, 50 – 60 Hz
Max. pull force	1000N
Max. door area	15 m ²
Max. door weight	100kg balanced door
Max. door height	2400 – 3500mm
Drive mechanism	Chain / Belt
Opening / Closing speed	160mm / Second
LED	24V / 15pcs LED bulbs
Limit setting	Electronic
Transformer	Overload protection technology
Radio frequency	433.92 MHz
Coding format	Rolling code (7.38 x 10 ¹⁹ Combinations)
Transmitter	2X
Code storage capacity	25 different codes
Caution light terminal	Included
Working temperature	-40°C – +50°C
Safety protection	Soft start & Soft stop Caution light
Protection level	IP20

ACCESSORIES



PE SAFETY BEAMS*

For added safety, this allows the garage door to automatically reverse when its sensory light beam is broken by an obstruction, helping to protect your family from injury and your car from the damage caused by contact.



WIRELESS KEYPAD

Weatherproof digital keypad with cover which can be programmed with codes from 1 to 6 digits, for maximum security. Includes back-light for your convenience when used in poor lighting situations.



EC04 REMOTE HANDSET

Comes with 4 buttons which act as multi-functional hand transmitters. It can also be programmed to open different garage doors or gates on the one-handset.



WALL SWITCH*

Can be installed near an internal access door to your garage giving you greater convenience to open and close your garage door.



VEHICLE SUN VISOR REMOTE*

For the convenience of clipping onto your vehicles visor. Operates up to 3 Garage Door Openers.

* Options available

MELBOURNE (Head Office)

181-183 Frankston-Dandenong Rd,
Dandenong South Vic 3175

t: (03) 9703 1500

e: sales@ecogaragedoors.com.au

www.ecogaragedoors.com.au

SYDNEY

Unit 6, 72 Lasso Road,
Gregory Hills NSW 2557

t: (02) 8417 8117